

DELHI TOWERS

Non-Penetrating Roof Mounts & Tripods



Non-Penetrating Roof Mounts

- Pre-galvanized steel frame.
- Accommodates patio stones and concrete blocks.
- Heavy duty construction.
- Accepts up to 2.5" mast (mast not included).
- UPS shippable.

NPRM-1

Mast clamp height 51" (1.3 m), 34 lbs (15.5 kg)

NPRM-1/2

Mast clamp height 51" (1.3 m), 26 lbs (11.8 kg)



Tripod Roof Mounts

- 1 1/4" (3.18 cm) galvanized welded steel tubing.
- Accepts up to 1 3/4" (4.4 cm) mast.
- Heavy duty construction.
- Swing away mast support.

TRM-2

2' (0.61 m), 6.8 lbs (3.1kg)
Leg distance 24"

TRM-3

3' (0.91 m), 8 lbs (3.63 kg)
Leg distance 32"

TRM-3P

As above individually packaged

TRM-3PL

As above individually packaged including PPLS

TRM-5

5' (1.52 m), 13 lbs (5.9 kg)
Leg distance 44"

TRM-5P

As above individually packaged

TRM-5PL

As above individually packaged including PPLS

TRM-10

10' (3 m), 50 lbs (22.73 kg)
Leg distance: 78"

PPLS

Three butyl sealing pads
Six 2" (5.1 cm) lag screws

TR2-5

Bi-pod. 5' (1.52 m), 7 lbs (3.18 kg)

3 Tripod PipeB

3 foot tripod packaged with 3 foot
1.66" O.D. Mast, 14 Ga

